

MP SERIES FOR TRASH AND CLEAN WATER

Whenever it is necessary to move large quantities of water, whether during flooding, or simply filling a pond, these petrol powered pumps can move it quickly and efficiently.

UP TO
1340 Lt/min
FLOW



Inlet, Outlet Pipes



MOTOR PUMPS	MP36-2	MP56-3	MP34-2	MP66-3
PUMP				
TYPE	Semitrash	Semitrash	Trash	Trash
HEAD m	30	26	30	27
FLOW L/min	600	930	700	1340
SPEED rpm	3600	3600	3600	3600
INPUT/OUTPUT DIAMETER inch	2	3	2	3
MAX DIAMETER ALLOWED mm			20	27
ENGINE				
BRAND	Honda	Honda	Honda	Honda
MODEL	GX120	GX160	GX160	GX240
FUEL	petrol	petrol	petrol	petrol
DISPLACEMENT cc	118	163	163	242
CYLINDER	1 inclined	1 inclined	1 inclined	1 inclined
COOLING SYSTEM	Air	Air	Air	Air
STARTING SYSTEM / ELECTRIC CIRCUIT (volt)	Recoil	Recoil	Recoil	Recoil
CONSUMPTION				
CONSUMPTION at 75% of load L/h	1,0	1,4	1,0	1,5
TANK CAPACITY L	2,5	3,6	3,6	6,0
RUNNING TIME at 75% of load h	2,5	2,5	3,5	3,9
NOISE EMISSION				
NOISE LEVEL LWA dB(A)	103	105	106	110
ACOUSTIC PRESSURE at 7 m dB(A)	78	80	78	83
DIMENSIONS AND WEIGHT				
LENGTH mm	506	525	653	672
WIDTH mm	402	399	474	516
HEIGHT mm	421	476	641	680
WEIGHT (dry) Kg	24	34	48	59
STANDARD EQUIPMENT, OPTION AND ACCESSORIES (x: Standard, o: Optional)				
OIL GUARD SYSTEM	x	x	x	x
3 JUBILEE PIPE CLIPS	x	x	x	x
2 THREADED COUPLINGS	x	x	x	x
FILTER	x	x	x	x
SPARK PLUG TOOL	x	x	x	x
INLET PIPES 2", 3" LENGTH 8/25 m	o	o	o	o
OUTLET PIPE 2", 3" LENGTH 5/10/50/100 m	o	o	o	o

** On electric version +3/8 Kg to add