

# P INVERTER SERIES

## THE ACCURATE ENERGY

The right power to supply equipment sensitive to voltage surges.

Weight  
21 Kg



P3000i

P4500i

	P2000i single phase	P3000i single phase	P4500i single phase
<b>THREE PHASE</b>			
(POWER LTP) kW/kVA			
(POWER COP) kW/kVA			
<b>SINGLE PHASE</b>			
(POWER LTP) kW/kVA	1,65/1,65	2,80/2,80	4,30/4,30
(POWER COP) kW/kVA	1,35/1,35	2,50/2,50	3,80/3,80
<b>POWER SPECIFICATIONS</b>			
VOLTAGE V	230	230	230
FREQUENCY Hz	50	50	50
POWER FACTOR cosΦ	1,0	1,0	1,0
<b>ENGINE</b>			
BRAND	Robin	Robin	Robin
MODEL	EH09-2	EX17	EX27
FUEL	petrol	petrol	petrol
DISPLACEMENT cc	86	169	265
SPEED	variable	variable	variable
CYLINDER	1 vertical	1 inc. angle	1 inc. angle
COOLING SYSTEM	air	air	air
STARTING SYSTEM	Recoil	Recoil	Recoil/Electric
<b>CONSUMPTION</b>			
CONSUMPTION at 75% of load L/h	0,58	1,25	1,66
TANK CAPACITY L	4	11	13
RUNNING TIME at 75% of load h	6,0	8,6	7,7
<b>NOISE EMISSION</b>			
NOISE PRESSURE LEVEL at 7 m dB(A)	59	58	62
GUARANTEED SOUND POWER LEVEL LWA dB(A)	91	90	93
<b>DIMENSIONS AND WEIGHT</b>			
LENGTH mm	490	537	580
WIDTH mm	295	482	527
HEIGHT mm	445	583	618
WEIGHT (dry) Kg	21	54	74
<b>SOCKET TYPE</b>			
	2 x SCHUKO	2 x SCHUKO	2 x SCHUKO
<b>ALTERNATOR AND SOCKET PROTECTION</b>			
ELECTRIC PROTECTION	IP 23	IP 23	IP 23
SOCKET PROTECTION	IP 54	IP 54	IP 44