

PW SERIES

DIRECT AND GEARBOX TRANSMISSION

Easily transportable and ready to use; this is the ideal machine for a myriad of professional and residential uses.

TRANSPORTATION
KIT STANDARD



PW3000



PW150

HIGH PRESSURE WASHERS	PW1500	PW150	PW3000	PW240	PW3000
PUMP					
MAX PRESSURE bar/psi	110/1600	150/2200	200/2900	240/3500	200/2900
FLOW L/min	11,4	11,4	15,0	12,5	15,0
SPEED rpm	1750	3400	1450	3400	1450
ENGINE					
BRAND	Honda	Honda	Honda	Honda	Yanmar
MODEL	GX160	GX160	GX340	GX390	L100
FUEL	petrol	petrol	petrol	petrol	diesel
DISPLACEMENT cc	163	163	337	389	435
CYLINDER	1 inclined	1 inclined	1 inclined	1 inclined	1 vertical
COOLING SYSTEM	Air	Air	Air	Air	Air
STARTING SYSTEM / ELECTRIC CIRCUIT (volt)	Recoil	Recoil	Recoil	Electric/Recoil	Electric
CONSUMPTION					
CONSUMPTION at 75% of load L/h	1,0	1,0	2,0	2,5	1,5
TANK CAPACITY L	3,6	3,6	6,5	6,5	5,5
RUNNING TIME at 75% of load h	3,5	3,6	3,2	2,7	3,6
NOISE EMISSION					
NOISE LEVEL LWA dB(A)	107	106	110	103	108
ACOUSTIC PRESSURE at 7 m dB(A)	82	81	85	78	83
DIMENSION AND WEIGHT					
LENGTH mm	700	630	1040	951	1040
WIDTH mm	490	580	590	765	590
HEIGHT mm	890	540	790	655	790
WEIGHT (dry)** Kg	44	32	72	64	117
STANDARD EQUIPMENT, OPTIONS AND ACCESSORIES (x: Standard, o: Optional)					
OIL GUARD SYSTEM	x	x	x	x	
2:1 GEAR BOX	x		x		x
DIRECT DRIVE		x		x	
CHEMICAL INJECTION	x	x	x	x	x
PRESSURE HOSE	x	x	x	x	x
SUCTION HOSE WITH STRAINER			x		x
INLINE FILTER	x	x	x	x	x