

# LIGHT GLOBE & LIGHT TOWER

## POWERFUL LIGHT

With a high luminosity power, the LIGHT GLOBE and LIGHT TOWER are the innovative easy-to-use solutions for many activities: sport events, building yards, night harvest, emergency needs.



	GLOBE DIAMETER	LIT UP AREA	LUMEN	VOLTAGE/FREQ	MAST	PROTECTION	LAMP	MAX WIND SPEED	MAX HEIGHT	OPERATION TEMPERATURE	WEIGHT
	cm	m <sup>2</sup>		V/Hz		LEVEL	W/type	Km/h	m	°C	Kg
LIGHT GLOBE 750 H	55	310	11.400	230/50	included	IP 54	750 W Halogen	30	2,8	-25/+45	5
LIGHT GLOBE 2.0 H	110	1500	54.000	230/50	optional	IP 53	2000 W Halogen	100	5,0	-25/+45	10
LIGHT GLOBE 4.0 H Mobil	100	3000	108.000	230/50	included	IP 54	4000 W Halogen	80	5,0	- 25/+45	105
LIGHT GLOBE 1.0 HTI	110	2200	80.000	230/50	optional	IP 53	1000 W HTI*	100	5,0	- 25/+45	20
LIGHT GLOBE 1.2 HMI	110	2500	110.000	230/50	optional	IP 53	1200 W HMI*	100	5,0	- 25/+45	30

### HOT RESTRIKE

\* with ballast included

	LAMP	LUMEN	LIT UP AREA	LAMP	VOLTAGE/FREQ	ELEVATION	LAMP AUTONOMY	MAX HEIGHT	OPERATION TEMPERATURE	PROTECTION	WEIGHT
	W		m <sup>2</sup>	type	V/Hz	type	hours	m	°C	LEVEL	Kg
LIGHT TOWER Stand Alone	up to 6.000	up to 132.000	up to 2250	Halogen	230/50	Pneumatic	2.000	4,2	-5/+130	IP 55	20
LIGHT TOWER for Portable*	up to 6.000	up to 132.000	up to 2250	Halogen	230/50	Pneumatic	2.000	4,2	-5/+130	IP 55	20
LIGHT TOWER 400Wx6	2.400	192.000	2500	Metal Halide	400/50	Hydraulic	5.000	9,0	-5/+130	IP 55	630
LIGHT TOWER 1500Wx6	9.000	200.000	1200	Halogen	400/50	Hydraulic	4.000	9,0	-5/+130	IP 55	630
LSW 10 1000Wx4	4.000	340.000	4500	Metal Halide	230/50	Hydraulic	10.000	9,0	-5/+130	IP 55	1010

\* Elevation type (Compressed air) | Telescopic shaft sliding sections (3)